

SANDIA REPORT

SAND2015-

Unlimited Release

Printed December 2015

Approximate Augmentation of Turbulent Law-of-the-Wall by Periodic Free-Stream Disturbances

Lawrence J. DeChant

Prepared by
Sandia National Laboratories
Albuquerque, New Mexico 87185 and Livermore, California 94550

Sandia National Laboratories is a multi-program laboratory managed and operated by Sandia Corporation, a wholly owned subsidiary of Lockheed Martin Corporation, for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-AC04-94AL85000.

Approved for public release; further dissemination unlimited.



Issued by Sandia National Laboratories, operated for the United States Department of Energy by Sandia Corporation.

NOTICE: This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from
U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831

Telephone: (865) 576-8401
Facsimile: (865) 576-5728
E-Mail: reports@adonis.osti.gov
Online ordering: <http://www.osti.gov/bridge>

Available to the public from
U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Rd.
Springfield, VA 22161

Telephone: (800) 553-6847
Facsimile: (703) 605-6900
E-Mail: orders@ntis.fedworld.gov
Online order: <http://www.ntis.gov/help/ordermethods.asp?loc=7-4-0#online>



Approximate Augmentation of Turbulent Law-of-the-Wall by Periodic Free-Stream Disturbances

Lawrence J. DeChant
Aerosciences Department
Sandia National Laboratories
P.O. Box 5800
Albuquerque, New Mexico 87185-0825

ABSTRACT

We examine the role of periodic sinusoidal free-stream disturbances on the inner law law-of-the-wall (log-law) for turbulent boundary layers. This model serves a surrogate for the interaction of flight vehicles with atmospheric disturbances. The approximate skin friction expression that is derived suggests that free-stream disturbances can cause enhancement of the mean skin friction. Considering the influence of grid generated free stream turbulence in the laminar sublayer/log law region (small scale/high frequency) the model recovers the well-known shear layer enhancement suggesting an overall validity for the approach. The effect on the wall shear associated with the lower frequency due to the passage of the vehicle through large (vehicle scale) atmospheric disturbances is likely small i.e. on the order 1% increase for turbulence intensities on the order of 2%. The increase in wall pressure fluctuation which is directly proportional to the wall shear stress is correspondingly small.

ACKNOWLEDGMENTS

The authors would like to thank Justin Smith and Ross Wagnild; Aerospace Department, Sandia for their technical insight and support.

CONTENTS

Abstract	3
Acknowledgments.....	4
Contents	5
Figures.....	5
Tables	5
Nomenclature	5
I. Introduction.....	8
II. Analysis.....	9
A. Pulsatile Flow	9
B. Pulsatile Inner Law	11
C. Disturbance Frequency Estimate	18
III. Results.....	20
A. Small Scale, High Frequency, Isotropic Grid Induced Free-Stream Turbulence.....	20
B. Large Scale Free-Stream Disturbances	23
IV. Conclusions.....	24
V. References.....	24
VI. Distribution	25

FIGURES

Figure 1. Comparison between full integral expression and the approximation expressed in equation (22).	16
Figure 2. Skin friction enhancement due to free stream turbulence using equation (26)	21

TABLES

Table 1. Root-mean-square wall pressure expressions	9
Table 2.. Estimates for vehicle turbulent boundary layer frequency scales. Estimated magnitudes follow for $v_w=1 \times 10^{-4}$ m ² /s, $U_\infty=1000$ m/s, $L_{\text{vehicle}}=1$ m and $Re_x=1E8$	19

NOMENCLATURE

Symbols

a Dimensionless model constant

B	Inner aw constant B=5
c	Locally defined constant
C_f	Skin friction $C_f = \frac{2\tau_w}{\rho U^2}$
C_{f_0}	Undisturbed free-stream skin friction
I	Turbulence intensity (absolute value)
K	Clauser turbulent viscosity constant
L	Streamwise length scale
p'	Root Mean Square (RMS) pressure fluctuation amplitude
Re	Reynolds number
Re_s	Stokes Reynolds number: $Re_s = \frac{\Delta U_\infty \sqrt{\frac{2\nu_w}{\omega}}}{\nu_w}$
Re_x	Streamwise flat plate Reynolds number
Re_θ	Momentum thickness Reynolds number
t	time
u	Streamwise turbulent mean flow
U	Free stream turbulent mean flow velocity
U^+	Inner law velocity free stream U/v^*
u'	Root Mean Square (RMS) streamwise velocity fluctuation amplitude
u^+	Inner law velocity u/v^*
v'	Root Mean Square (RMS) cross-stream velocity fluctuation amplitude
v^*	Friction velocity $v^* = \sqrt{\frac{\tau_w}{\rho}}$
x	Streamwise spatial coordinate
y	Cross-stream spatial coordinate
y^*	y/δ
y^+	Cross-stream inner law length scale $y^+ = \frac{yv^*}{\nu_w}$

Greek

δ	Boundary layer thickness
δ^+	Boundary layer thickness inner law length scale $\delta^+ = \frac{\delta v^*}{\nu_w}$
ΔU_∞	Pulsatile flow streamwise velocity amplitude
η	Pulsatile flow similarity independent variable: $\eta = y \sqrt{\frac{\omega}{\nu_{eff}}}$
κ	Von Karman constant $\kappa=0.41$
$\tilde{\kappa}$	Pulsatile flow modified Von Karman constant
ν	Kinematic viscosity
ω	Pulsatile flow frequency
ρ	Density
τ	Shear stress
θ	Momentum thickness

Subscripts/Superscripts

eff	Turbulent effective
inc	Incompressible
FT	Fully Turbulent
max	Maximum
os	Laminar-turbulent pressure “over-shoot”
rms	Root Mean Square (RMS)
s	Steady
turb	Turbulent
t, tran	Transition
vehicle	Reentry vehicle
w	Wall
∞	Steady free-stream constant

I. INTRODUCTION

To this point, we have modeled reentry vehicle boundary layer induced loading assuming a steady (or more properly slowly varying) approach and captured stochastic (atmospheric) perturbations using a direct pressure loading approach. This decoupled modeling with associated superposition provides a reasonable approach however there is value in attempting to ascertain the couple effect of disturbance on the boundary layer loading.

The effect of free-stream turbulence on skin friction is well known e.g. Simonich and Bradshaw (1978), Meier and Kreplin (1980), and Blair and Werle (1980), Kondjoyan (2002). These results suggest a significant, i.e. as much as (20-30%) increase in wall shear due to free stream turbulence. Correlations are available to estimate this increase as a function of turbulence intensity, e.g. the result by Simonich and

Bradshaw $\frac{C_f}{C_{f_0}} = 1 + 2I$ where C_f is the skin friction, C_{f_0} is the unenhanced skin friction and I is the

turbulence intensity. See DeChant (2015) for additional discussion.

Though the effect of free-stream turbulence characterized by length scales that are the order of the boundary layer thickness or smaller and frequencies that are correspondingly large, is well understood, the effect of low-moderate frequency large scale free-stream disturbances is not readily available. Indeed we suggest that large scale disturbances of this type are perhaps best modeled as unsteady pulsatile free-stream disturbances where a temporal frequency is specified. There is little direct information regarding this type of model regarding skin friction so we propose to test the result by considering it in the small scale/high frequency limit. The classical free-stream turbulence skin friction enhancement should be recovered in the high frequency limit. With some sense of the viability of the model, the behavior of the lower frequency encounter can then be estimated.

We have a particular interest in the skin friction since wall pressure fluctuation root-mean-square values are well correlated with the mean wall shear. $p_w' \propto \tau_w$. The proportionality “constant” varies considerably range from 2-6. Moreover, the “constant value” is likely Reynolds number dependent as suggested by Farabee and Casarella (1991), Bernardini and Pirozzoli (2011) and DeChant (2015) as suggested in table 1.

Researcher	Model ($\frac{p_w'}{\tau_w}$)	Value $Re_x=1 \times 10^8$
Farabee and Casarella (1991)	$\frac{p_w'}{\tau_w} = \sqrt{6.5 + 1.86 \ln(\frac{\delta^+}{333})}$	3.90
Bernardini and Pirozzoli (2011)	$\frac{p_w'}{\tau_w} = \sqrt{2.27 \ln(\delta^+) - 7.36}$	4.05
DeChant (2005)	$\frac{p_w'}{\tau_w} = 1.828(\delta^+)^{0.0681}$	3.74

Table 1. Root-mean-square wall pressure expressions

For our purposes it is likely sufficient to describe the RMS wall pressure to mean wall shear as approximately four, i.e. $p_w' \approx 4\tau_w$. These paragraphs suggest that modeling the effect of unsteady fluctuation encounters on the wall shear stress will provide a first order loading estimate.

II. ANALYSIS

A. Pulsatile Flow

A simplified modeling approach for free-stream fluctuation encounter is considered here. The fluctuation is presumed to take the form: $U(x, t) = U_\infty + \Delta U_\infty \cos(\omega t)$. Our focus is the wall shear stress expression and we can therefore restrict our modeling efforts to:

$$\left(\frac{\partial u}{\partial t} - \frac{\partial U}{\partial t} \right) = \frac{\partial}{\partial y} \left(\nu^* \kappa y \frac{\partial u}{\partial y} \right) \quad (1)$$

Where we have (consistent with traditional near wall modeling) we have neglected the convective acceleration terms. See DeChant (2015) for a related analysis.

We are interested in a near wall model and will construct expressions that fundamentally retain steady turbulent wall layer behavior, specifically, local law of the wall profiles. To achieve this goal, we will use an iteration procedure rather than the more classical perturbation series. Let's then consider the outer-law dominated unsteady flow:

$$\frac{\partial u}{\partial t} - \frac{\partial U}{\partial t} = \frac{\partial}{\partial y} \left(\nu_{eff} \frac{\partial u}{\partial y} \right) \quad (2)$$

Where ν_{eff} is a turbulent effective viscosity. We will require that it be a constant or at most a function of

the streamwise local “x”. “Obvious” choices would include: $\nu_{eff} = KU_{\infty}\delta$, $\nu_{eff} = C \frac{U_{\infty}}{\nu^*} \nu_w$ where:

K	=	Clauser constant 0.016,
δ	=	local (steady) boundary layer thickness
ν_w	=	wall molecular viscosity
ν^*	=	friction velocity
U_{∞}	=	steady free-stream velocity

To solve equation (2) we propose that a solution takes the form:

$$u \approx u_s(y) + \Delta U_{\infty} \cos \omega t - \Delta U_{\infty} f(\eta) \cos(\omega t - a\eta) \quad ; \quad \eta = y \sqrt{\frac{\omega}{\nu_{eff}}} \quad (3)$$

Substitution of this expression into equation (2) yields an expression in terms of $\cos(\omega t - a\eta)$ and $\sin(\omega t - a\eta)$. Demanding that both the cosine and sine expressions are individually satisfied yields two linear equations for $f(\eta)$ of the form:

$$2a \frac{df}{d\eta} + f = 0 \rightarrow f = \exp\left(-\frac{1}{2a} \eta\right) \quad (4)$$

and

$$\frac{d^2 f}{d\eta^2} - a^2 f = 0 \rightarrow f = \exp(-a\eta) \quad (5)$$

Obviously, these two expressions can represent the same functional behavior by choosing “a” such that

$$\frac{1}{2a} = a \rightarrow a = \frac{\sqrt{2}}{2} \quad (6)$$

which yields $a = \frac{\sqrt{2}}{2}$. We can thus, estimate that the (unsteady) term is now:

$$\begin{aligned} u &= \Delta U_{\infty} \left(\cos \omega t - \exp\left(-\frac{\sqrt{2}}{2} \eta\right) \cos\left(\omega t - \frac{\sqrt{2}}{2} \eta\right) \right) \\ &= \Delta U_{\infty} \left(\cos \omega t - \exp\left(-\sqrt{\frac{\omega}{2\nu_{eff}}} y\right) \cos\left(\omega t - \sqrt{\frac{\omega}{2\nu_{eff}}} y\right) \right) \end{aligned} \quad (7)$$

The steady portion of equation (3) $u_s(y)$ would be governed by $0 = \frac{\partial}{\partial y} \left(\nu_{eff} \frac{\partial u_s}{\partial y} \right)$. Though we are unlikely gain a useful estimate for laminar from this type of expression since it is only valid near the wall (we would need something like $U_\infty \frac{\partial u_s}{\partial x} = \frac{\partial}{\partial y} \left(\nu_{eff} \frac{\partial u_s}{\partial y} \right)$) there is still value in considering laminar flow for the unsteady portion. Laminar flow with $\nu_{eff} = \nu_w$ yields wall shear (Arpaci and Larsen, (1984)) as:

$$\begin{aligned} \frac{\tau_w}{\rho} &= -\nu_{eff} \frac{\partial u}{\partial y} \Big|_{y=0} \\ &= -\nu_{eff} \frac{\partial u_s}{\partial y} \Big|_{y=0} + \nu_{eff} \Delta U_\infty \sqrt{\frac{\omega}{\nu_{eff}}} \cos(\omega t + \frac{\pi}{4}) \end{aligned} \quad (8)$$

Where we have used: $\cos(\omega t + \frac{\pi}{4}) = \frac{\sqrt{2}}{2} (\cos(\omega t) - \sin(\omega t))$. This expression is not terribly useful in this form, however, since the problem of interest involves turbulent flow.

B. Pulsatile Inner Law

Let's then consider equation (2) $\frac{\partial u}{\partial t} - \frac{\partial U}{\partial t} = \frac{\partial}{\partial y} \left(\nu_{eff} \frac{\partial u}{\partial y} \right)$ where we formally integrate with respect to “y” to give:

$$\int_0^\infty \left(\frac{\partial u}{\partial t} - \frac{\partial U}{\partial t} \right) dy + \frac{\tau_w}{\rho} = \nu^* \kappa y \frac{\partial u}{\partial y} \quad (9)$$

Certainly to proceed, we need to be able to estimate the LHS of equation (9). If we use our unsteady estimate for velocity $u = u_s(y) + \Delta U_\infty \left(\cos \omega t - \exp(-\frac{\sqrt{2}}{2} \eta) \cos(\omega t - \frac{\sqrt{2}}{2} \eta) \right)$ i.e. equation (9) we find that:

$$\int_0^\infty \left(\frac{\partial u}{\partial t} - \frac{\partial U}{\partial t} \right) dy = \frac{\sqrt{2}}{2} \Delta U_\infty \sqrt{\nu_{eff} \omega} \cos(\omega t + \frac{\pi}{4}) \quad (10)$$

We can then write:

$$\frac{\sqrt{2}}{2} \frac{\Delta U_\infty}{\kappa \nu^* y} \sqrt{\nu_{eff} \omega} \cos(\omega t + \frac{\pi}{4}) + \frac{\nu^*}{\kappa y} = \frac{du}{dy} \quad (11)$$

Which we can integrate to give:

$$\begin{aligned} \frac{u}{v^*} &= \frac{1}{\kappa} \left(\frac{\sqrt{2}}{2} \frac{\sqrt{v_{eff}} \omega \Delta U_{\infty}}{v^{2*}} \cos(\omega t + \frac{\pi}{4}) + 1 \right) \ln(y) + c(x, t) \\ &= \frac{1}{\kappa} \left(\frac{\sqrt{2}}{2} \frac{\sqrt{v_{eff}} \omega \Delta U_{\infty}}{v^{2*}} \cos(\omega t + \frac{\pi}{4}) + 1 \right) \ln\left(\frac{yv^*}{v_w}\right) + C(x, t) \end{aligned} \quad (12)$$

Traditionally for a steady flow we would modify the constant in equation (12) to include

$\frac{1}{\kappa} \ln(y) + c = \frac{1}{\kappa} \ln\left(\frac{yv^*}{v_w}\right) - \frac{1}{\kappa} \ln\left(\frac{v^*}{v_w}\right) + C$, however, it is less clear how one should modify the

associated constant, i.e. should there be a net unsteady effect? Moreover, the constant certainly must honor the wall boundary condition which for steady flow would simply imply that

$u^+ = \frac{u}{v^*} = \frac{1}{\kappa} \ln\left(\frac{yv^*}{v_w}\right) + B$ By way of guidance simulation and measurements described in Ribas and

Deschamps (2004) suggest that flow within the laminar sublayer is independent of the pulsatile behavior which implies that the wall function $C(x, t)$ should be $C=B=5.0$

Using this constant we can then write the pulsatile flow modified law-of-the-wall as:

$$u^+ = \frac{1}{\kappa} \left(\frac{\sqrt{2}}{2} \frac{\Delta U_{\infty} \sqrt{v_{eff}} \omega}{v^{2*}} \cos(\omega t + \frac{\pi}{4}) + 1 \right) \ln y^+ + B \quad (13)$$

The steady law-of-the-wall model is well understood but the scaling associated with the unsteady term requires additional consideration. Following Arpaci and Larsen the laminar wall friction can be shown to be:

$$\frac{\tau'_{w_lam}}{\rho} = v_w \Delta U_{\infty} \sqrt{\frac{\omega}{2v_w}} \cos(\omega t + \frac{\pi}{4}) \quad (14)$$

If we intend to ignore the particular temporal behavior associated with a disturbance we can easily replace the periodic function by the associated root-mean square magnitude as:

$\left| \left(\frac{\Delta U_{\infty}}{U_{\infty}} \right)^2 \text{Re}_s^{-1} \cos(\omega t + \frac{\pi}{4}) \right| \rightarrow \left(\frac{\Delta U_{\infty}}{U_{\infty}} \right)^2 \text{Re}_s^{-1}$. The magnitude associated with the unsteady term is

easily assessed but the sign is less readily apparent since either sign is plausible using the pulsatile external flow. We suggest, however, that the net effect of external disturbances will be associated with a favorable pressure gradient implying that we should utilize a negative sign for the unsteady term which permits us to write:

$$u^+ = \frac{1}{\kappa} \left(1 - \left(\frac{\nu_{eff}}{\nu_w} \right)^{1/2} \left(\frac{\tau_{w_lam}}{\tau_{w_turb}} \right) \left| \frac{\tau'_{w_lam}}{\tau_{w_lam}} \right| \right) \ln y^+ + B \quad (15)$$

Let's estimate the size of the terms in equation (15). Using the Clauser constant (White (2006)) to estimate the effective viscosity we can write:

$$1. \quad \left(\frac{\nu_{eff}}{\nu_w} \right)^{1/2} \approx 0.127 \text{Re}_\delta^{1/2} = 0.05 \text{Re}_x^{3/7}$$

$$2. \quad \frac{\tau_{w_lam}}{\tau_{w_turb}} \approx 25 \text{Re}_x^{-5/14}$$

So that $\left(\frac{\nu_{eff}}{\nu_w} \right)^{1/2} \left(\frac{\tau_{w_lam}}{\tau_{w_turb}} \right) \approx O(2) \text{Re}_x^{1/14}$.

Of more interest is the ratio between the steady laminar and periodic shear magnitudes:

$$\frac{\nu_w \Delta U_\infty \sqrt{\frac{\omega}{2\nu_w}}}{U_\infty^2} = \left(\frac{\Delta U_\infty}{U_\infty} \right)^2 \text{Re}_s^{-1} \text{ where } \text{Re}_s \text{ is the Stokes Reynolds number } \text{Re}_s = \frac{\Delta U_\infty \sqrt{\frac{2\nu_w}{\omega}}}{\nu_w}. \text{ Notice}$$

that for low frequency, $\text{Re}_s \gg 1$ and that for high frequency $\text{Re}_s \ll 1$.

Using these expressions we can write:

$$u^+ \approx \frac{1}{\kappa} \left(1 - 2 \text{Re}_x^{1/14} \left(\frac{\Delta U_\infty}{U_\infty} \right)^2 \text{Re}_s^{-1} \right) \ln y^+ + B \quad (16)$$

Equation (16) provides a high frequency periodic modification to the law-of-the wall.

Equation (16) is a modified law-of-the-wall which can be used to estimate a periodic flow sensitive skin friction expression. To do this, we consider the inner variable derivation for flat plate skin friction. A classically useful model based upon inner variables is developed by White (2004). In this derivation one solves the approximate momentum equation:

$$\rho u \frac{\partial u}{\partial x} \approx \frac{\partial \tau}{\partial y} \quad (17)$$

where τ is assumed to be the turbulent stress only. Utilizing the inner variables: $u = v^* u^+$ where v^* is the friction velocity $v^* = \left(\frac{\tau_w}{\rho}\right)^{1/2}$. Note that the wall shear and the thereby friction velocity are functions of

“x”, and $\frac{\partial}{\partial y} = \frac{\partial}{\partial y^+} \frac{\partial y^+}{\partial y} = \frac{v^*}{v_w} \frac{\partial}{\partial y^+}$ since $y^+ = \frac{v^* y}{v_0}$, Thus equation (17) can be written:

$$v^* \frac{dv^*}{dx} (u^{+2}) \approx \frac{v^*}{\rho v_w} \frac{\partial \tau}{\partial y^+} \quad (18)$$

Following White we now integrate between the wall and the boundary layer thickness (in terms of inner variables) as:

$$\frac{dv^*}{dx} \int_0^{\delta^+} u^{+2} dy^+ \approx -\frac{1}{\rho v_0} \tau_w = -\frac{v^{*2}}{v_w} \quad (19)$$

The kernel of the integral in equation (19) $\int_0^{\delta^+} u^{+2} dy^+$ is where the unsteady behavior associated with equation (16) is utilized.

The basic structure of equation (16) is essentially consistent with the traditional steady law-of-the-wall

$u^+ = \frac{1}{\tilde{\kappa}} \ln y^+ + B$ except the $\ln y^+$ coefficient is modified as

$\tilde{\kappa} = \kappa \left(1 - 2 \text{Re}_x^{1/14} \left(\frac{\Delta U_\infty}{U_\infty} \right)^2 \text{Re}_s^{-1} \right)^{-1}$ where $\kappa=0.41$ and $B=5.0$. Note that for small disturbances we can

write: $\tilde{\kappa} \approx \kappa \left(1 + 2 \text{Re}_x^{1/14} \left(\frac{\Delta U_\infty}{U_\infty} \right)^2 \text{Re}_s^{-1} \right)$ The integral is computed as:

$$\int_0^{\delta^+} u^{+2} dy^+ = \frac{\delta^+}{\kappa} \left((\ln \delta^+)^2 + 2(B-1) \ln \delta^+ + (B^2 \tilde{\kappa}^2 - 2\tilde{\kappa} + 2) \right) \quad (20)$$

This expression appears to be of rather limited value since it contains the inner law boundary layer thickness, however we can eliminate δ^+ using the law of the wall evaluated at $y=\delta$, i.e.

$U^+ = \frac{U}{v^*} = \frac{1}{\tilde{\kappa}} \ln \delta^+ + B$ so we have:

$$\frac{1}{\tilde{\kappa}} \ln \delta^+ = U^+ - B \quad (21)$$

$$\delta^+ = \exp(\tilde{\kappa}(U^+ - B)) = \frac{\exp \tilde{\kappa}(U^+)}{\exp(\tilde{\kappa}B)}$$

So that the integral becomes:

$$\int_0^{\delta^+} u^{+2} dy^+ = \frac{\exp \tilde{\kappa}(U^+)}{\exp(\tilde{\kappa}B)} \left(\tilde{\kappa}(U^+ - B)^2 + 2(B-1)(U^+ - B) + (B^2 \tilde{\kappa}^2 - 2\tilde{\kappa} + 2) \right) \quad (22)$$

The form of the integral in equation (22) suggests that it will be convenient to work in the variable U^+ rather than v^* itself. Notice that by using $v^* = \frac{U}{U^+}$; $\frac{dv^*}{dx} = -\frac{U}{U^{+2}} \frac{dU^+}{dx}$ can readily rewrite equation (19) as:

$$\frac{U}{U^{+2}} \frac{dU^+}{dx} \int_0^{\delta^+} u^{+2} dy^+ = \frac{1}{v_0} \frac{U^2}{U^{+2}} \quad (23)$$

$$\frac{dU^+}{d\text{Re}_x} \int_0^{\delta^+} u^{+2} dy^+ = 1$$

Equation (23) is a first order ODE that can be solved for U^+ as a function of Re_x and once we have solved

for U^+ one has immediate access to the skin friction since $U^+ = \left(\frac{2}{C_f} \right)^{1/2} \rightarrow C_f = \frac{2}{U^{+2}}$.

The form of the integral in equation is complex and can be simplified. For the steady flow problem with

$\tilde{\kappa} = \kappa$ where $\kappa=0.41$ and $B=5.0$, White suggests that $\int_0^{\delta^+} u^{+2} dy^+ \approx 8 \exp(0.48U^+)$. White actually uses

the more complete Spalding's law-of-the-wall to estimate the form of the integral, but the difference between the current log-law and the Spalding's closure is small. Since White's (2006) approximate result is only valid for the steady problem it cannot be used here, however, examination of the terms in equation (22) suggests that:

$$\frac{\exp(\tilde{\kappa}U^+)}{\exp(\tilde{\kappa}B)} \left(\tilde{\kappa}(U^+ - B)^2 + 2(B-1)(U^+ - B) + (B^2 \tilde{\kappa}^2 - 2\tilde{\kappa} + 2) \right) \approx \frac{3}{2} U^{+2} \frac{\exp(\tilde{\kappa}U^+)}{\exp(\tilde{\kappa}B)} \quad (22)$$

We plot this result for $\tilde{\kappa} = \kappa$ where $\kappa=0.41$ and $B=5.0$




Figure 1. Comparison between full integral expression and the approximation expressed in equation (22).

Comparison between full integral expression equation (22) and the approximation

$$\frac{3}{2} \tilde{\kappa} U^{+2} \frac{\exp(\tilde{\kappa} U^+)}{\exp(\tilde{\kappa} B)} \text{ for } \tilde{\kappa} = \kappa \text{ where } \kappa=0.41 \text{ and } B=5.0$$

Though this approximate integral $\frac{3}{2} \tilde{\kappa} U^{+2} \frac{\exp(\tilde{\kappa} U^+)}{\exp(\tilde{\kappa} B)}$ can utilized in equation (23) there is value (which will become apparent subsequently) in following White in attempting to approximate the integral by

$$\frac{3}{2} \tilde{\kappa} U^{+2} \frac{\exp(\tilde{\kappa} U^+)}{\exp(\tilde{\kappa} B)} \approx C_0 \exp(\tilde{\kappa} C_1 U^+). \text{ An examination of White's result for } \tilde{\kappa} = \kappa \text{ where } \kappa=0.41 \text{ and}$$

$$B=5.0 \text{ suggests that } \frac{3}{2} \tilde{\kappa} U^{+2} \frac{\exp(\tilde{\kappa} U^+)}{\exp(\tilde{\kappa} B)} \approx \frac{3}{2} \tilde{\kappa} \frac{(10)^2}{\exp(\tilde{\kappa} B)} \exp(1.17 \tilde{\kappa} U^+) \text{ will provide a reasonable}$$

$$\text{comparison since } \frac{3}{2} \tilde{\kappa} \frac{(10)^2}{\exp(\tilde{\kappa} B)} \approx 7.9 \text{ thus recapitulating Whites approximate expression.}$$

$$\text{Utilizing the approximate integral form } \frac{150 \tilde{\kappa}}{\exp(\tilde{\kappa} B)} \exp(1.17 \tilde{\kappa} U^+) \text{ in equation (23) we can write the}$$

separable first order differential equation:

$$\frac{U}{U^{+2}} \frac{dU^+}{dx} \int_0^{\delta^+} u^{+2} dy^+ = \frac{1}{\nu_0} \frac{U^2}{U^{+2}} \quad (23)$$

$$\frac{150\tilde{\kappa}}{\exp(\tilde{\kappa}B)} \int \exp(1.17\tilde{\kappa}U^+) dU^+ = \text{Re}_x$$

The integral $\int U^{+2} \exp \tilde{\kappa}(U^+) dU^+$ follows as:

$$\frac{U}{U^{+2}} \frac{dU^+}{dx} \int_0^{\delta^+} u^{+2} dy^+ = \frac{1}{\nu_0} \frac{U^2}{U^{+2}} \quad (24)$$

$$\frac{128.2}{\exp(\tilde{\kappa}B)} \exp(1.17\tilde{\kappa}U^+) = \text{Re}_x$$

This equation in terms of U^+ can be solved as:

$$U^+ = \frac{1}{1.17\tilde{\kappa}} \ln \left(\frac{1}{128.2} \exp(\tilde{\kappa}B) \text{Re}_x \right) \quad (25)$$

Using the relationship for $C_f = \frac{2}{U^{+2}}$ we can write:

$$C_f = \frac{2(1.17)^2 \tilde{\kappa}^2}{\ln^2 \left(\frac{1}{128.2} \exp(\tilde{\kappa}B) \text{Re}_x \right)} = \frac{2.74\tilde{\kappa}^2}{\ln^2 (0.0078 \exp(5\tilde{\kappa}) \text{Re}_x)} \quad (26)$$

Where we recall that $\tilde{\kappa} = \kappa \left(1 - 10 \left(\frac{\Delta U_\infty}{U_\infty} \right)^2 \text{Re}_s^{-1} \right)^{-1} \approx \kappa \left(1 + 10 \left(\frac{\Delta U_\infty}{U_\infty} \right)^2 \text{Re}_s^{-1} \right)$. Let's examine this

expression for $\tilde{\kappa} = \kappa$ and $B=5$ so as to write: $C_f = \frac{0.460}{\ln^2 (0.06 \text{Re}_x)}$. This expression compares well

with White's steady flow classical flat plate formula which is written: $C_f = \frac{0.455}{\ln^2 (0.06 \text{Re}_x)}$

With access to the effect of a disturbance within the skin friction model via equation (26) it is of particular importance to us is to assess the size of the term: $\left(\frac{\Delta U_\infty}{U_\infty}\right)^2 \text{Re}_s^{-1}$ where Re_s is the Stokes

Reynolds number $\text{Re}_s^{-1} = \frac{\sqrt{2}}{2} \frac{\sqrt{\omega \nu_w}}{\Delta U_\infty}$ whereby: $2 \text{Re}_x^{1/4} \left(\frac{\Delta U_\infty}{U_\infty}\right)^2 \text{Re}_s^{-1} = \sqrt{2} \text{Re}_x^{1/4} \left(\frac{\Delta U_\infty}{U_\infty}\right) \frac{\sqrt{\omega \nu_w}}{U_\infty}$.

C. Disturbance Frequency Estimate

The size of the frequency term $\frac{\sqrt{\omega \nu_w}}{U_\infty}$ is obviously an essential part of the problem. The size of the frequency term follows from the external forcing and the local or near wall viscous boundary layer flow field. For true pulsatile or periodic flow, the frequency is externally imposed and is well characterized while for encounters with free-stream disturbances of various scales it is less well known.

Here we consider a family of velocity scales and length scales that permit estimation of the dimensionless frequency term $\frac{\sqrt{\omega \nu_w}}{U_\infty}$. In table 2 we present a family of length and velocity scales associated with

external, outer boundary layer and inner variable boundary layer behavior. Length scale range from a maximum of vehicle scale $O(1\text{m})$ to a small scale of laminar sublayer $O(1\text{E-}7\text{ m})$. Velocity scales follow from a maximum of free-stream $O(1000\text{ m/s})$ to a minimum of the friction velocity $v^* = \frac{\sqrt{2}}{2} C_f^{1/2} U_\infty \approx O(100\text{m/s})$. Frequency estimates follow using a velocity scale divided by the

length scale. A very wide range of scales is possible. Via the equilibrium assumption, large scale disturbances must transmit their energy through to Kolmogorov scale (Tennekes and Lumley (1972))

which will imply a large frequency $\left(\frac{\delta v_w^3}{U_\infty^3}\right)^{-1/4} U_\infty = O(E9)$ and a relatively large dimensionless

frequency $\frac{\sqrt{\omega \nu_w}}{U_\infty} \approx O(1) - O(1\text{E} - 1)$. This large frequency estimate is consistent with the well-known

k- ω turbulence model “rough wall”. boundary condition (See Wilcox 2002) where $\omega_{wall} = \frac{2500\nu_w}{k_r^2}$

where “k” is an effective roughness length scale. Wilcox recommends that

$$k^+ = 5 \rightarrow k = 5 \frac{\nu_w}{v^*} \approx \frac{5\sqrt{2}}{\sqrt{C_f}} \frac{\nu_w}{U_\infty}. \text{ Using this value we estimate that: } \omega_{wall} = O\left(\frac{100C_f U_\infty^2}{\nu_w}\right) \approx O(1E9)$$

Length	Velocity	Frequency ω	$\frac{\sqrt{\omega \nu_w}}{U_\infty}$	$\frac{\sqrt{\omega \nu_w}}{U_\infty}$ Order of Magnitude*	Comment
L_{vehicle}	U_∞	$\frac{U_\infty}{L_{\text{vehicle}}}$	$\text{Re}_{L_{\text{vehicle}}}^{-1/2}$	O(1E-4)	Vehicle transit
δ	U_∞	$\frac{U_\infty}{\delta}$	$\text{Re}_\delta^{-1/2}$	O(1E-3)	Outer B.L.
$\frac{\nu_w}{U_\infty}$	U_∞	$\frac{U_\infty^2}{\nu_w}$	1	1	Laminar sublayer
$\left(\frac{\delta \nu_w^3}{U_\infty^3}\right)^{1/4}$	U_∞	$\left(\frac{\delta \nu_w^3}{U_\infty^3}\right)^{-1/4} U_\infty$	$\text{Re}_\delta^{-1/8}$	O(1E-1)	Kolmogorov
δ	v^*	$\frac{v_w^*}{\delta}$	$\left(\frac{v^*}{U_\infty}\right)^{1/2} \text{Re}_\delta^{-1/2}$	O(1E-5)	Inner/Outer transition
$\frac{\nu_w}{U_\infty}$	v^*	$\frac{v^* U_\infty}{\nu_w}$	$\left(\frac{v^*}{U_\infty}\right)^{1/2}$	O(1E-2)	Log Law
$\left(\frac{\delta \nu_w^3}{U_\infty^3}\right)^{1/4}$	v^*	$\left(\frac{\delta \nu_w^3}{U_\infty^3}\right)^{-1/4} v^*$	$\left(\frac{v^*}{U_\infty}\right)^{1/2} \text{Re}_\delta^{-1/4}$	O(1E-3)	Inner law Kolmogorov

Table 2.. Estimates for vehicle turbulent boundary layer frequency scales. Estimated magnitudes follow for $\nu_w=1 \times 10^{-4}$ m²/s, $U_\infty=1000$ m/s, $L_{\text{vehicle}}=1$ m and $\text{Re}_x=1E8$.

We will examine two classes of frequency behavior: (1) Flow dominated by basically isotropic free-stream turbulence with high frequency content that is dominated by the smallest possible viscous scale. This behavior is the classical grid generated free-stream boundary layer interaction problem for which we have significant data which can be used to substantiate the analytical development of the model and (2)

flow dominated by the passage of a reentry vehicle through atmospheric disturbances, the problem of particular interest here, but where we have little data with which to ascertain the validity of the estimates.

III. RESULTS

A. Small Scale, High Frequency, Isotropic Grid Induced Free-Stream Turbulence

“Small scale” isotropic free-stream turbulence is usually generated by grids upstream of the flow test section and is primarily characterized by a turbulence intensity, which for our purposes is given by

$\left(\frac{\Delta U_\infty}{U_\infty}\right)$. The smallest frequency associated with the free-stream can be estimated from

$\omega_{grid} = \frac{U_\infty}{\lambda}$ where λ is the Taylor micro-scale length scale (Roach 1987). For grid induce turbulence the

Taylor microscale is related to grid mesh diameter “d” and the distance from the grid. A more useful result for a free flight vehicle is to correlate the Taylor micro-scale to the associated boundary layer

thickness as: $\lambda \approx \delta \text{Re}_\delta^{-1/2}$. The associated Kologorov scale $\left(\frac{\delta v_w^3}{U_\infty^3}\right)^{-1/4} U_\infty$ with the length scale λ

would them imply that the dimensionless frequency is $\frac{\sqrt{\omega v_w}}{U_\infty} = \text{Re}_\delta^{-1/16}$. Thus, one can estimate:

$\frac{\tilde{\kappa}}{\kappa} \approx 1 + \sqrt{2} \left(\frac{\Delta U_\infty}{U_\infty}\right)$ where we estimate that $\frac{\text{Re}_\delta^{1/14}}{\text{Re}_\delta^{1/16}} = O(1)$. The magnitude of the external disturbances

is rather more easily estimated with $\left(\frac{\Delta U_\infty}{U_\infty}\right) \approx I$ where “I” is the turbulence intensity. Using the closure

suggested by we can readily estimate the increase in skin friction associated with free-stream turbulence.

We plot:




Figure 2. Skin friction enhancement due to free stream turbulence using equation (26)

Figure 2. provides a depiction of the skin friction enhancement due to free stream turbulence using

equation (26) with $C_f = \frac{2.74\tilde{\kappa}^2}{\ln^2(0.0078 \exp(5\tilde{\kappa}) \text{Re}_x)}$ and $\tilde{\kappa} \approx \kappa(1 + \sqrt{2I})$. Due to the importance of

estimating the enhancement of skin friction (and by the Reynolds analogy) heat transfer associate with free-stream turbulence a number of researchers have proposed analytical and semi-empirical based expressions (Kondjoyan et. al. 2002) to estimate the skin friction enhancement. Simonich and Bradshaw (1978) provide a simple (and well regarded) classical model as:

$$\frac{C_f}{C_{f_0}} = 1 + 2I \quad (27)$$

Where $C_{f_0} = C_f(I = 0)$. A similar model discussed by Meier and Kreplin (1980) takes the form:

$$\frac{C_f}{C_{f_0}} = \begin{cases} 190I^2 & 0 < I < 0.01 \\ 3.8I - 0.019 & I > 0.01 \end{cases} \quad (28)$$

An empirical model proposed by Blair and Werle (1980) explicitly includes Reynolds number information in the formulation as:

$$\frac{C_f}{C_{f_0}} = 0.98 + 1.92 \left(\frac{\text{Re}_\theta}{1000} \right)^{0.4} \quad (29)$$

where Re_θ is the momentum thickness Reynolds number. We can relate Re_θ to Re_x as:
 $Re_\theta \approx 0.015 Re_x^{6/7}$.

Figure 2 compares the skin friction enhancement using equation (26), and the three models, i.e. equations (27), (28) and (29) for $Re_x=1E5$ (low) and $Re_x=1E7$. We see from figure 2 that for the low (transitional) Reynolds number that the current model, the Simonich and Bradshaw expression and the Blair and Werle expressions are in good agreement. The Meier and Kreplin expression tends to over-predict the skin friction enhancement. At the higher (and more practical) Reynolds number $Re_x=1E7$ the explicit

Reynolds number dependence associated with equation (29) $\frac{C_f}{C_{f_0}} = 0.98 + 1.92 \left(\frac{Re_\theta}{1000} \right)^{0.4}$ is not viable for Reynolds numbers larger than $Re_x=5E5$.




Figure 3. Comparison between analytical estimate via equation (26) and the classical/semi-empirical models equations (27), (28) and (29) for (a) $Re_x=1E5$ and (b) $Re_x=1E7$. Equation (29) while useful for $Re_x=1E5$ is not applicable for the higher Reynolds number.

Figure 3. suggests that derived expression, i.e. equation (26) is viable to provide estimates for skin friction enhancement due to free-stream turbulence which suggests that this approach may be viable for large scale free-stream effects.

B. Large Scale Free-Stream Disturbances

Our focus is on the boundary layer skin friction enhancement effect associated with the flight of reentry vehicles through atmospheric disturbances. Utilizing this approach for the large scale problem may be possible by examining frequency estimates consistent with the transit of the vehicle through large scale disturbances. A simple estimate of frequency, say, $\omega_{vehicle} = \frac{U_{\infty}}{L_{vehicle}} = O(1E3)Hz$ would seem appropriate. Let's examine some very rough estimates for the terms in this expression:

$$\begin{aligned} v_w &= 1 \times 10^{-4} \text{ m}^2/\text{s} \\ U_{\infty} &= 1000 \text{ m/s} \\ L_{vehicle} &= 1 \text{ m} \end{aligned}$$

We immediately see that the vehicle scale is much larger than the Taylor scale:

$$\frac{\lambda}{L_{vehicle}} \propto \frac{\delta}{L} \propto \text{Re}_x^{-9/7} \lll 1$$

As before, the external excitation, regardless of the source will ultimately be dissipated via the Kolmogorov scales and frequencies. Hence an essential computation will be the Kolmogorov frequency

as estimated using $\left(\frac{L_{vehicle} v_w^3}{U_{\infty}^3} \right)^{-1/4} U_{\infty}$ that implies that $\frac{\sqrt{\omega v_w}}{U_{\infty}} \propto L_{vehicle}^{-1/8} \propto \text{Re}_x^{-1/8}$. For the notional

value of $\text{Re}_x = O(1E8)$ we expect that $\frac{\sqrt{\omega v_w}}{U_{\infty}} \propto O\left(\frac{1}{10}\right)$. This value is an order of magnitude smaller than

the homogeneous turbulence behavior discussed previously. Nonetheless, this effect could be important suggesting that we should examine atmospheric free-stream turbulence intensity magnitudes. A survey by Reidel and Sitzmann (1998) suggest that so called clear air turbulence intensity is less than 0.1% while flights through observable clouds can be very large with fluctuation on the order of 1-10%. In all cases, these intensities were measured using subsonic aircraft where the associated free-stream velocities were from 100-200 m/s. For a notional velocity of 1000 m/s we could expect that clear air turbulence intensities may be on the order of 0.02% while observable clouds are less than 2%

A basic upper bound estimate for passage of a high speed vehicle through observable clouds suggests that

$I=O(2\%)$ and $\frac{\sqrt{\omega v_w}}{U_\infty} \propto O(\frac{1}{10})$ whereby we estimate that $\frac{C_f}{C_{f_0}} \approx 1.01$. This suggests that large

scale/external disturbances may induce a relatively small increase in wall pressure and may be safely ignored for a preliminary modeling effort.

IV. CONCLUSIONS

A classical inner law model for wall friction has been modified to include the effect of a periodic sinusoidal free-stream for turbulent boundary layers. This model serves a surrogate for the interaction of flight vehicles with atmospheric disturbances. Consistent with experience, the skin friction expression that is derived suggests that free-stream disturbances can cause enhancement of the mean skin friction. Considering the influence of grid generated free stream turbulence in the laminar sublayer/log law region (small scale/high frequency) the model recovers the well-known shear layer enhancement suggesting an overall validity for the approach. The effect on the wall shear associated with the lower frequency due to the passage of a reentry vehicle through large (vehicle scale) atmospheric disturbances is likely small i.e. on the order 1% increase for turbulence intensities on the order of 2%. The increase in wall pressure fluctuation which is directly proportional to the wall shear stress is shown to be correspondingly small.

V. REFERENCES

1. Arpaci, V. S., Larsen, P. S., *Convection Heat Transfer*, Prentice-Hall, Englewood Cliffs, NJ, 1984.
2. Bernardini, M., Pirozzoli, S., "Wall Pressure Fluctuation Beneath Supersonic Turbulent Boundary Layers," *Phys. Fluids*, 23, 8, 085102, 2011.
3. Blair, M. F., Werle, M. J. "The Influence of Free-Stream Turbulence on the Zero Pressure Gradient Fully Turbulent Boundary Layer," 1980, ADA-101089, <http://www.dtic.mil/cgi-bin/GetTRDoc?Location=U2&doc=GetTRDoc.pdf&AD=ADA101089>
4. DeChant, L. J., "A Root Mean Square Pressure Fluctuation Model Using Inner Law Concepts with Extensions to Laminar-Turbulent Transitional Flows," SAND-2015-6607.
5. DeChant, L. J., "Approximate Model for Turbulent Stagnation Point Flow," SAND-2015-xxxx.
6. DeChant, L. J., "Estimation of Several Turbulent Fluctuation Quantities Using an Approximate Pulsatile Flow Model" SAND-2015-xxxx.

7. Farabee, T. M., Casarella, M. J., "Spectral Features of Wall Pressure Fluctuations Beneath Turbulent Boundary Layers," *Phys. Fluids A*, 3,10, October, 1991, pp. 2410-2420.
8. Kondjoyan, A., Peneau, F., Boisson, H. "Effect of High Free Stream Turbulence on Heat Transfer between Plates and Air Flows: a Review of Existing Experimental Results," *Int. J. Thermal Science*, 41, 2002, 1-16.
9. Meier, H. U., Kreplin, "Influence of Free-Stream Turbulence on Boundary Layer Development," *AIAA Journal*, 18, 1, 1980, 11-15.
10. Reidel, H., Sitzmann, M., "In-Flight Investigation of Atmospheric Turbulence," *Aerosciences and Technology*, V2, 5, pp. 301-319, 1998.
11. Ribas, F., Deschamps, C. J., "Friction Factor Under Transient Flow Condition," International Compressor Engineering Conference School of Mechanical Engineering, 2004, <http://docs.lib.purdue.edu/icec/index.7.html>
12. Roach, P. E., "The Generation of Nearly Isotropic Turbulence by Means of Grids," *Int. J. of Heat and Fluid Flow*, V.8, 2 1987, 82-92.
13. Simonich, J. C., Bradshaw, P., "Effect of Free-Stream Turbulence on Heat Transfer Through a Turbulent Boundary layer," *J. Heat Transfer*, 1978, pp. 671-677.
14. Tennekes, H., Lumley, J. L., *A First Course in Turbulence*, MIT Press, Cambridge, MA, 1972.
15. White, F. M., *Viscous Fluid Flow* 3rd ed., McGraw-Hill, NY, 2006.
16. Wilcox, D. C., *Turbulence Modeling for CFD*, DCW Industries, La Canada, CA, 2002

VI. DISTRIBUTION

1	MS0346	Richard Field	1526 (electronic copy)
1	MS0346	Mikhail Mesh	1523 (electronic copy)
1	MS0825	Steven Beresh	1515 (electronic copy)
1	MS0825	Lawrence DeChant	1515 (electronic copy)
1	MS0825	Jeff Payne	1515 (electronic copy)
1	MS0825	Justin Smith	1515 (electronic copy)
1	MS9018	Central Technical Files	8944 (electronic copy)
1	MS0899	Technical Library	4536 (electronic copy)

